



# **ACED2420**



- 24 X 20W high-power RGBALC 6in1 Leds
- LumenRadio W-DMX (optional)
- Excellent linear dimming and color mixing effects
- Seetronic IP PowerCON TRUE1 and XLR connectors
- Easy-to-use diffuser and barndoor (optional)



Source: 24X20W 6-IN-1 RGBALC

LEDs

Flicker free operation for broadcast

TV and FILM

Life Span: 50,000 hours

The life span may vary depending on several following factors but not

limited to:

Environmental Conditions, Power/ Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming, etc)

#### **Optics**

24PCS high efficiency acrylic lens 25° /35° /45° Lens optional Easy-to-use diffuser fliter (customization options) Easy-to-use 8 way barndoors (optional)

#### Colors

Sophisticated 6 colors RGBALC mixed Even and soft light coverage with pure mixing Preset color macros

#### Strobe Effect

0-25Hz high speed shutter/strobe effect with variable speed

#### **Dimming System**

0-100% Smooth linear LED dimming Smoother dimming mode available

#### **Control System**

10/14/17/21 DMX channels DMX512, RDM, Master-slave, Auto, W-DMX (optional) Multi preset internal programs Shielded input signal protection for stable signal without interference Seetronic IP65 3-Pin or 5-Pin XLR connectors IN/OUT

### **Display System**

1.77" TFT LCD display

English/Chinese menu 4 control touch buttons 180° Reversible for LCD display Display auto OFF

#### **Cooling System**

Active, Forced Air, Temperature regulated
Over temperature protection management

### **Power Supply**

600W Power supply AC100-240V 50/60Hz Seetronic IP65 PowerCON TRUE1 IN/ OUT

#### Housing

Aluminium, steel, plastic PC/ASA, rubber, Lens PE and tempered glass front

Tilt angle manually adjustable Two side handles on base Exterior finish: Black

#### Installation

2\*1/4 turn fastening Omega Clamps 1\*Safety attachment point

#### **Operating Condition**

Operating positions: all (device on floor or fixed to a support) -25° to 45° ambient temperature IP65 protection rating

## Weight

N.W.: 6.6kg

### Dimensions

Product Dimensions: 420(D)\*140(W)\*265(H)mm



#### **Accessories**




8-way Barndoors (Optional)



Diffuser (Optional)

# **Dimension**



# **Photometrics**

