

ACED2420S



- 24 X 20W high-power RGBW 4in1 Leds
- 6 individually controllable segments
- LumenRadio W-DMX (optional)
- Excellent linear dimming and color mixing effects
- Seetronic IP Power TRUE1 and XLR connectors
- Easy-to-use diffuser and barndoor (optional)



Light Source

Source: 24X20W 4-IN-1 RGBW LEDs
 Flicker free operation for broadcast TV and FILM
 Life Span: 50,000 hours
 The life span may vary depending on several following factors but not limited to:
 Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming, etc)

Optics

24PCS high efficiency acrylic lens
 25° /35° /45° Lens optional
 Easy-to-use diffuser fliter (customization options)
 Easy-to-use 8 way barndoors (optional)

Colors

6 Segments controllable individually
 Sophisticated 4 colors RGBW mixed
 Even and soft light coverage with pure mixing
 Preset color macros

Strobe Effect

0-25Hz high speed shutter/strobe effect with variable speed

Dimming System

0-100% Smooth linear LED dimming
 Smoother dimming mode available

Control System

8/13/16/21/25/41 DMX channels
 DMX512, RDM, Master-slave, Auto, W-DMX (optional)
 Multi preset internal programs
 Shielded input signal protection for stable signal without interference
 Seetronic IP65 3-Pin or 5-Pin XLR connectors IN/OUT

Display System

1.77" TFT LCD display

English/Chinese menu

4 control touch buttons
 180° Reversible for LCD display
 Display auto OFF

Cooling System

Active, Forced Air, Temperature regulated
 Over temperature protection management

Power Supply

600W Power supply
 AC100-240V 50/60Hz
 Seetronic IP65 PowerCON TRUE1 IN/OUT

Housing

Aluminium, steel, plastic PC/ASA, rubber, Lens PE and tempered glass front
 Tilt angle manually adjustable
 Two side handles on base
 Exterior finish: Black

Installation

2*1/4 turn fastening Omega Clamps
 1*Safety attachment point

Operating Condition

Operating positions:
 all (device on floor or fixed to a support)
 -25° to 45° ambient temperature
 IP65 protection rating

Weight

N.W.: 6.6kg


Dimensions

Product Dimensions:
 420(D)*140(W)*265(H)mm

Accessories




8-way Barndoors (Optional)



Diffuser (Optional)

Dimension





Photometrics

Distance (meter)
Distance (feet)

1m
3.3ft

3m
9.8ft

5m
16.4ft



Color

- RED
- GREEN
- BLUE
- WHITE
- RGBW full

78000lx
30000lx
64000lx
50000lx
120000lx

9400lx
2330lx
6500lx
5550lx
13100lx

4000lx
1130lx
2190lx
1940lx
5000lx