



个人微信号:DFS10001



微信公众平台:DFS-888



公司网站

QUALITY MAKE BETTER LIFE



ADVANCED . MODE . INDIVIDUATION



深圳市东升创科技有限公司
DFS TECH (SHEN ZHEN) CO.,LTD.

ADD: Fu Ting Industrial Area Guan-Lan Town ShenZhen
City Guang Dong Province Of China

TEL: 86-755-29051386 86-755-28037763

Hot line:13923437553

SKYPE: dfsfork

QQ: 2654298429 旺旺: dfs气叉

EMAIL: eastlu@dfsfork.com

Http:// www.dfsfork.cn

https://dfsfork.en.alibaba.com



DFS

东方升 DongFangSheng

WWW.DFSFORK.CN





第 18554575 号

商标注册证

civet

核定使用商品/服务项目（国际分类：12）

第12类：自行车、脚踏车支架（自行车、脚踏车部件）；自行车；自行车车把；自行车支架；电动运载工具；自行车车架；折叠行李车；自行车轮胎；自行车车圈；自行车车座（截止）

注册人 深圳市东升创科技有限公司

注册人地址 广东省深圳市宝安区观澜街道新城社区竹村西区福庭工业区五栋四楼东北分隔体

注册日期 2017年01月21日 有效期至 2027年01月20日

局长

刘俊臣

发证机关



第 19514347 号

商标注册证

DFS
东方升 DongFangSheng

核定使用商品/服务项目（国际分类：12）

第12类：自行车撑脚架；自行车车把；自行车车圈；自行车轮胎；自行车；自行车车架；电动自行车（截止）

注册人 深圳市东升创科技有限公司

注册人地址 广东省深圳市宝安区观澜街道新城社区竹村西区福庭工业区五栋四楼东北分隔体

注册日期 2017年08月28日 有效期至 2027年08月27日

局长

刘俊臣

发证机关



第 16083366 号

商标注册证

high-cool

注册人 深圳市东升创科技有限公司

注册人地址 广东省深圳市宝安区观澜街道新城社区竹村西区福庭工业区五栋四楼东北分隔体

注册日期 2016年03月07日 有效期至 2026年03月06日

局长

许瑞表

发证机关



第 18400123 号

商标注册证



核定使用商品/服务项目（国际分类：12）

第12类：自行车支架；自行车、脚踏车支架（自行车、脚踏车部件）；自行车、脚踏车车把；自行车曲柄；自行车、脚踏车车架；自行车；脚踏车；自行车、脚踏车或摩托车车座；脚踏车马达；自行车、脚踏车辐条（截止）

注册人 深圳市东升创科技有限公司

注册人地址 广东省深圳市宝安区观澜街道新城社区竹村西区福庭工业区五栋四楼东北分隔体

注册日期 2017年09月28日 有效期至 2027年09月27日

局长

刘俊臣

发证机关



FREE RIDE SERIES

MODEL: DFS-RLC-TP-36

WHEEL: 26" & 27.5" 29"
PITCH: 144MM
STANCHION: 36MM AL 7050/HARD ANODIZED
STEERER TUBE: 39.8MM—28.6MM TP AL7050
LOWER: ONE PIECE MAGNESIUM
CROWN: FORGED AL 6061 T6
SPRING: ADJUST AIR SPRING
NEGATIVE: AIR SPRING
BUSHING: TEFLON
LOCK OUT: NO
REBOUND: ADJUST WITH HYDRAULIC
HIGH & LOW SPEED COMPRESSION DAMPING
TRAVEL: 150MM
DISC MOUNTS: POST
WEIGHT: 2.1KG
AXLE STYLE: 15x110

- 气压可调；
- AL 7050铝竖管；
- 36MM AL 7050铝内管；
- 负压气室
- 镁合金外脚；
- DU滑套；
- 回弹阻尼可调；
- 高低速压缩阻尼
- 含油海棉圈；
- 内管硬质阳极
- 行程150MM
- 桶轴15X110



MODEL: DFS-RLC-TP-RCE-TC-BOOST-15X110

WHEEL: 29"
 PITCH: 125MM
 STANCHION: 32MM AL 7050/Hard Anodized
 STEERER TUBE: Carbon 39.8mm—28.6mm TP
 LOWER: Carbon
 CROWN: Carbon
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION
 REBOUND: ADJUST WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.35KG
 AXLE STYLE: 15x110

- 气压可调；
- 一体式碳纤维竖管+肩盖；
- 32MM AL 7050铝内管；
- 负压弹簧；
- 碳纤维外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海棉圈；
- 内管硬质阳极极
- 行程100MM
- 桶轴15X110



MODEL: DFS-RLC-TP-RCE-TC-15X110

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 32MM AL 7050/Hard Anodized
 STEERER TUBE: Carbon 39.8mm—28.6mm tp
 LOWER: Carbon
 CROWN: Carbon
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: REMOTE CONTROL HYDRAULIC WITH
 COMPRESSION
 REBOUND: ADJUST WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.4KG

- 气压可调；
- 一体式碳纤维竖管+肩盖；
- 32MM AL 7050铝内管；
- 负压弹簧；
- 碳纤维外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海棉圈；
- 内管硬质阳极
- 行程100MM
- 桶轴15X110



MODEL: DFS-RLC-TP-RCE-TC-15X100

WHEEL: 26" & 27.5" 29"

PITCH: 125MM

STANCHION: 32MM AL 7050/Hard Anodized

STEERER TUBE: Carbon 39.8mm—28.6mm TP

LOWER: Carbon

CROWN: Carbon

SPRING: ADJUST AIR SPRING

NEGATIVE: COIL+MCU

BUSHING: TEFLON

LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION

REBOUND: ADJUST WITH HYDRAULIC

TRAVEL: 100MM

DISC MOUNTS: POST

WEIGHT: 1.4KG



- 气压可调；
- 一体式碳纤维竖管+肩盖；
- 32MM AL 7050铝内管；
- 负压弹簧；
- 碳纤维外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海绵圈；
- 内管硬质阳极
- 行程100MM
- 桶轴15X100

MODEL: DFS-RLC-TP-RCE-TC

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 32MM AL 7050/Hard Anodized
 STEERER TUBE: Carbon 39.8mm—28.6mm tp
 LOWER: Carbon
 CROWN: Carbon
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: REMOTE CONTROL HYDRAULIC WITH
 COMPRESSION
 REBOUND: ADJUST WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.398KG

- 气压可调；
- 一体式碳纤维竖管+肩盖；
- 32MM AL 7050铝内管；
- 负压弹簧；
- 碳纤维外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海棉圈；
- 内管硬质阳极
- 行程100MM
- 轴9X100





MODEL: DFS-RLC-TP-RCE-32-15X110

- WHEEL: 26" & 27.5" 29"
- PITCH: 125MM
- STANCHION: 32MM AL 7050/HARD ANODIZED
- STEERER TUBE: 39.8MM—28.6MM TP AL7050
- LOWER: ONE PIECE MAGNESIUM
- CROWN: FORGED AL 6061 T6
- SPRING: ADJUST AIR SPRING
- NEGATIVE: COIL+MCU
- BUSHING: TEFLON
- LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION
- REBOUND: ADJUST WITH HYDRAULIC
- TRAVEL: 100MM
- DISC MOUNTS: POST
- WEIGHT: 1.55KG
- AXLE STYLE: 15X110



- 气压可调；
- AL 7050铝竖管；
- 32MM AL 7050铝内管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海绵圈；
- 内管硬质阳极
- 行程100MM；
- 桶轴15X110；

MODEL: DFS-RLC-TP-RCE-32-15X100

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 32MM AL 7050/HARD ANODIZED
 STEERER TUBE: 39.8MM—28.6MM TP AL7050
 LOWER: ONE PIECE MAGNESIUM
 CROWN: FORGED AL 6061 T6
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION
 REBOUND: ADJUST WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.55KG
 AXLE STYLE: 15X100

- 气压可调；
- AL 7050铝竖管；
- 32MM AL 7050铝内管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海棉圈；
- 内管硬质阳极
- 行程100MM；
- 桶轴15X100；



MODEL: DFS-RLC-TP-RCE-32

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 32MM AL 7050/HARD ANODIZED
 STEERER TUBE: 39.8MM—28.6MM TP AL7050
 LOWER: ONE PIECE MAGNESIUM
 CROWN: FORGED AL 6061 T6
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION
 REBOUND: ADJUST WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.5KG



- 气压可调；
- AL 7050铝竖管；
- 32MM AL 7050铝内管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海绵圈；
- 内管硬质阳极
- 行程100MM；
- 轴9X100；

MODEL: CIVET-RLC-TP-RCE-32-15X110

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 32MM AL 7050/HARD ANODIZED
 STEERER TUBE: 39.8MM—28.6MM TP AL7050
 LOWER: ONE PIECE MAGNESIUM
 CROWN: FORGED AL 6061 T6
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION
 REBOUND: ADJUST WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.59KG
 AXLE STYLE: 15X100

- 气压可调；
- AL 7075铝竖管；
- 32MM AL 7075铝内管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海绵圈；
- 内管硬质阳极
- 行程100MM；
- 桶轴15X110；





MODEL: CIVET-RLC-TP-RCE-32-15X100

- WHEEL: 26" & 27.5" 29"
- PITCH: 125MM
- STANCHION: 32MM AL 7050/HARD ANODIZED
- STEERER TUBE: 39.8MM—28.6MM TP AL7050
- LOWER: ONE PIECE MAGNESIUM
- CROWN: FORGED AL 6061 T6
- SPRING: ADJUST AIR SPRING
- NEGATIVE: COIL+MCU
- BUSHING: TEFLON
- LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION
- REBOUND: ADJUST WITH HYDRAULIC
- TRAVEL: 100MM
- DISC MOUNTS: POST
- WEIGHT: 1.59G
- AXLE STYLE: 15X100



- 气压可调；
- AL 7075铝竖管；
- 32MM AL 7075铝内管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海棉圈；
- 内管硬质阳极
- 行程100MM；
- 桶轴15X100；

MODEL: CIVET-RLC-32

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 32MM AL 7075/HARD ANODIZED
 STEERER TUBE: 1-1/8 AL7050
 LOWER: ONE PIECE MAGNESIUM
 CROWN: FORGED AL 6061 T6
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: MANUAL CONTROL HYDRAULIC WITH COMPRESSION
 REBOUND: ADJUST WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.55KG

- 气压可调；
- AL 7075铝竖管；
- 32MM AL 7075铝内管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 回弹阻尼可调；
- 线控锁死；
- 含油海棉圈；
- 内管硬质阳极
- 行程100MM；
- 轴9X100；





MODEL: COOL-LC-RCE-15X110

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 30MM BUTTED STEEL TUBE
 STEERER TUBE: 1-1/8 AL7075
 LOWER: ONE PIECE MAGNESIUM
 CROWN: FORGED AL 6061 T6
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION
 REBOUND: WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.89KG
 AXLE STYLE: 15X110



- 气压可调；
- AL 7075铝竖管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 线控锁死；
- 含油海棉圈；
- 内管钛色
- 行程100MM
- 桶轴15X110

MODEL: COOL-RLC-TP-RCE-15X100

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 30MM BUTTED STEEL TUBE
 STEERER TUBE: 39.8MM-28.6MM TP AL7050
 LOWER: ONE PIECE MAGNESIUM
 CROWN: FORGED AL 6061 T6
 SPRING: ADJUST AIR SPRING
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: REMOTE CONTROL HYDRAULIC WITH COMPRESSION
 REBOUND: ADJUST WITH HYDRAULIC
 TRAVEL: 100MM
 DISC MOUNTS: POST
 WEIGHT: 1.89KG
 AXLE STYLE: 15X100

- 气压可调；
- AL 7075铝竖管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 线控锁死；
- 含油海绵圈；
- 内管钛色
- 行程100MM
- 桶轴15X100





MODEL: COOL-LC

- WHEEL: 26" & 27.5" 29"
- PITCH: 125MM
- STANCHION: 30MM BUTTED STEEL TUBE
- STEERER TUBE: 1-1/8 AL7050
- LOWER: ONE PIECE MAGNESIUM
- CROWN: FORGED AL 6061 T6
- SPRING: ADJUST AIR SPRING
- NEGATIVE: COIL+MCU
- BUSHING: TEFLON
- LOCK OUT: HYDRAULIC WITH COMPRESSION
- REBOUND: WITH HYDRAULIC
- TRAVEL: 100MM
- DISC MOUNTS: POST
- WEIGHT: 1.85KG



- 气压可调；
- AL 7075铝竖管；
- 负压弹簧；
- 镁合金外脚；
- DU滑套；
- 肩控锁死；
- 含油海棉圈；
- 内管钛色
- 行程100MM
- 轴9X100

MODEL: ROLL-LC

WHEEL: 26" & 27.5" 29"
 PITCH: 125MM
 STANCHION: 30MM BUTTED STEEL TUBE
 STEERER TUBE: 1-1/8 AL7050
 LOWER: ONE PIECE MAGNESIUM
 CROWN: FORGED AL 6061 T6
 SPRING: COIL+MCU
 NEGATIVE: COIL+MCU
 BUSHING: TEFLON
 LOCK OUT: HYDRAULIC WITH COMPRESSION
 REBOUND: WITH HYDRAULIC
 TRAVEL: YES
 DISC MOUNTS: 100MM
 WEIGHT: POST
 AXLE STYLE: 2.0KG

- AL 7075铝竖管;
- 负压弹簧;
- 镁合金外脚;
- DU滑套;
- 肩控锁死;
- 含油海绵圈
- 行程100MM
- 轴 9X100



Intertek

TEST REPORT

APPLICANT: DPS MACHINE DESIGN INC.
FU TING INDUSTRIAL AREA,
GUAN-LAN TOWN, SHENZHEN CITY,
GUANG DONG PROVINCE OF CHINA

DATE: Jun 17, 2008

NUMBER: SZH00261481

ATTN: MR. LU

SAMPLE DESCRIPTION:
ONE (1) PIECE OF SUBMITTED SAMPLE SAID TO BE ROLL-TO SUSPENSION FORK.

COUNTRY OF ORIGIN: CHINA.

TESTS CONDUCTED:
AS REQUESTED BY THE APPLICANT, FOR DETAILS REFER TO ATTACHED PAGE(S)

CONCLUSION:
TESTED SAMPLE: FROCKING - ROLLING RATCHET TEST
STANDARD: AS PER CLAUSE 4.9.6 OF EN 14766-2005(B)

RESULT:
PASS

AUTHORIZED BY:
FOR INTERTEK TESTING SERVICES
SHENZHEN LTD.

HEN H.T. LIN
GENERAL MANAGER

Intertek Testing Services (Shenzhen) Ltd. (TWS) is a member of the Intertek Group of Companies. The Group is a leading provider of testing services in Hong Kong, Shenzhen, China. We are committed to providing high quality testing services to our customers. Attention is drawn to the terms and conditions printed overleaf.

PAGE 1 OF 2

Intertek

TEST REPORT

APPLICANT: DPS MACHINE DESIGN INC.
FU TING INDUSTRIAL AREA, GUAN-LAN TOWN,
SHENZHEN CITY, GUANG DONG PROVINCE OF
CHINA

DATE: Dec 04, 2008

NUMBER: SZH00332353

ATTN: LI DONG SHENG

SAMPLE DESCRIPTION:
ONE (1) PIECE OF SUBMITTED SAMPLE SAID TO BE :
ITEM NAME : SUSPENSION FORK.
REFERENCE NO. : 993 - A (P.1)

TESTS CONDUCTED:
AS REQUESTED BY THE APPLICANT, FOR DETAILS REFER TO ATTACHED PAGE(S)

CONCLUSION:
TESTED SAMPLE: FROCKING - ROLLING RATCHET TEST
STANDARD: AS PER CLAUSE 4.9.6 OF EN 14766-2005(B)

RESULT:
PASS

AUTHORIZED BY:
FOR INTERTEK TESTING SERVICES
SHENZHEN LTD.

HEN H.T. LIN
GENERAL MANAGER

Intertek Testing Services (Shenzhen) Ltd. (TWS) is a member of the Intertek Group of Companies. The Group is a leading provider of testing services in Hong Kong, Shenzhen, China. We are committed to providing high quality testing services to our customers. Attention is drawn to the terms and conditions printed overleaf.

PAGE 1 OF 2

作品登记证书

登记号: 国作登字-2014-F-00122761

作品名称: 东方升

作品类别: 美术作品

作者: 卢东升

著作权人: 深圳市东升创科技有限公司

创作完成时间: 2010年05月25日

首次发表时间: 2010年06月02日

以上事项, 由深圳市东升创科技有限公司申请, 经中国版权保护中心审核, 根据《作品自愿登记试行办法》规定, 予以登记。

登记日期: 2014年02月11日

登记机构签章

东方升 DongFangSheng

No. 00122761

作品自愿登记
专用章