

Labthink®



**Excellent Supplier of Packaging Testing
Instruments and Services**



Labthink Instruments Co., Ltd.

Combo Series

★ Oxygen / Water Vapor Transmission Rate Test System

Oxygen / Water Vapor Transmission Rate Test System is based on the testing principle of Coulometric oxygen sensor and infrared water vapor sensor. It is designed and manufactured according to ASTM D3985, ASTM F1249, ISO 15106-2 and other relevant standards to provide high precision and high efficiency oxygen and water vapor transmission rate tests for high and medium gas barrier materials. It is suitable for testing the oxygen and water vapor transmission performance of films, sheets and related materials in the fields of food, medicine, medical devices, daily chemicals, photovoltaic, electronic and many others.


C403H

3 cells with fully auto sample clamping


C406H

6 cells with easy magnetic sample holder


C401H

1 cell for both laminated materials and packages

Parameter		C401H	C403M	C403H	C406H
Test Range	cc / (m ² ·day) (50cm ²)	0.01 ~ 200	0.05 ~ 200	0.01 ~ 200	0.02 ~ 200
	g / (m ² ·day) (50cm ²)	0.005 ~ 50	0.05 ~ 40	0.005 ~ 40	0.02 ~ 40
	cc / (pkg·day)(Package)	0.00005 ~ 1	optional	optional	optional
	g / (pkg·day)(Package)	0.00002 ~ 0.25	optional	optional	optional
Resolution	cc / (m ² ·day)	0.0001	0.0001	0.0001	0.0001
	g / (m ² ·day)	0.0001	0.0001	0.0001	0.0001
Repeatability	cc / (m ² ·day)	0.01 or 1%	0.02 or 1%	0.01 or 1%	0.02 or 1%
	g / (m ² ·day)	0.005 or 2%	0.02 or 2%	0.005 or 2%	0.02 or 2%
Temperature	Range (°C)	15 ~ 50	15 ~ 50	15 ~ 50 5 ~ 60 (customized)	15 ~ 50 5 ~ 60 (customized)
	Fluctuation (°C)	±0.2	±0.2	±0.05	±0.15
Humidity	Range (%RH)	0%, 35 ~ 90%±2%	0%, 35 ~ 90%±2%	0%, 5 ~ 90%±2%	0%, 5 ~ 90%±2%, 100%
Test Cells	Pc	1 set (film+package)	3 sets	3 sets	6 sets

1 Gas Permeability

A Oxygen Transmission Rate Test System

This series of instruments can be used to measure the oxygen transmission rate of barrier materials with high and medium barrier properties with high accuracy and high efficiency. They are applicable to the determination of oxygen permeability of plastic films, sheeting, paper, and other packaging materials used in food, pharmaceutical, medical apparatus, consumer products, photovoltaic and electronic industries, etc. Optional accessories extend the capability to testing complete packages and systems such as bottles, pouches, cartons, blister packs, tubes and more.

Oxygen Transmission Rate (OTR) Test System is designed and manufactured based on the coulometric sensor method (aka.equal pressure method) and conforms to ASTM D3985 and ISO 15105-2.

Items	Model	C206H	C203H	C230H	C201H
Test Range	cc/(m ² ·day)	0.02~200	0.01~200	0.01~200	0.01~200 / 0.2~2000(optional)
	cc/(100in ² ·day)	/	/	0.0007~12.9	/
	cc/(pkg·day) (Package)	0.0001~1	0.00005~1	0.00005~1	0.00005~1
Resolution	cc/(m ² ·day)	0.0001	0.0001	0.001	0.0001
Repeatability	cc/(m ² ·day)	0.02 or 1% (whichever is greater)	0.01 or 1%, whichever is greater	0.01 or 2% (whichever is greater)	0.01 or 1% (whichever is greater)
Test Temperature	°C	15~50±0.15, 5~60 (Optional)	15~50±0.05, 5~60 (Optional)	10~55 ±0.2	15~50 ±0.2 (Optional)
Test Humidity	RH	0%, 5~90%±2%	O ₂ : 0%, 5~90%±1% Carrier Gas: 0%, 5~90%±2%	O ₂ : 0%, 5~90%±1% Carrier Gas: 0%, 5~90%±2%(Optional)	0%, 35~90%±2% (Standard) 100% (Optional)
Photos					

B Differential Pressure Method

This series of instruments can be used to measure the gas transmission rate, solubility coefficient, diffusion coefficient and permeability coefficient of plastic films, composite films, high-barrier materials, sheeting, foils and permeable membranes at various temperatures.

Oxygen Transmission Rate (OTR) Test System is designed and manufactured based on the differential-pressure method and conforms to ASTM D1434 and ISO 15105-1.

Items	Model	C106H	C130H	VAC-V2	C101H
Scope of application		films, sheeting	films, sheeting	films, sheeting	films, sheeting
Numbers of Test Cells		6 with independent test results	3 with independent test results	3 with independent test results	1 with independent test results
Test Range (cm ³ /m ² ·24h·0.1MPa)		0.01~50,000	0.01~50,000	0.05~50,000 (standard volume) At least 500,000 (extended volume)	0.01~50,000 (Standard) 0.01~500,000 (Optional)
Temperature Range		15°C~50°C, 5°C~60°C (Optional)	10°C~50°C (room temperature 23°C)	5°C~95°C	15°C~50°C
Temperature Fluctuation		±0.15°C	±0.05°C	±0.1°C	±0.2°C
Vacuum Resolution		0.01 Pa	0.01 Pa	0.1 Pa	0.05 Pa
Vacuum Degree of Test Chamber		≤ 10 Pa	<10 Pa	<20 Pa	< 10 Pa
Test Humidity		0%, 5~90%±2% (Customized)	Humidifying of test gas (customization available)	0%RH, 5%RH~95%RH (automatic humidification function under 10°C~40°C can be customized)	0%, 35~90%±2% (Customized)
Photos					

2 Water Vapor Permeability

By studying various test methods of water vapor transmission rate, Labthink manufactures many water vapor permeability testers based on ASTM E96 (gravimetric method), ISO 15106-2/ASTM F1249 (infrared sensor method), and ISO15106-3 (electrolytic sensor method). Labthink has the most complete product line of water vapor permeability testers in packaging industry worldwide.

A Infrared Sensor (Complies with ISO 15106-2, ASTM F1249, TAPPI T557.)

Items	Model	C306H	C303H	C390H	C301H
Test Range	g/(m ² ·d) (Standard)	0.02~40	0.005~40(standard), 0.005~100(optional)	0.005 ~ 40(standard),0.005 ~ 100(optional)	0.005 ~ 50
	g/(pkg·d) (Package)	0.0001~0.2	0.00002~0.2	0.000025 ~ 0.2	0.00002~0.25
Resolution	g/(m ² ·d)	0.0001	0.0001	0.0001	0.0001
Repeatability	g/(m ² ·d)	0.02 or 2% (whichever is greater)	0.005 or 2% (whichever is greater)	0.005 or 2% (whichever is greater)	0.005 or 2% (whichever is greater)
Test Temperature	℃	15~50, 5~60 (Optional)	15~50, 5~60 (Optional)	10 ~ 55 ±0.2	15 ~ 50 ±0.2
Test Humidity	RH	100%, 5~90%±2%	5~90%±1%	5% ~ 90% ±1%, 100%	0%, 35~90%±2% (Standard) 100% (Optional)
Photos					

B Gravimetric Method (Cup Method) (Complies with ISO 2528, ASTM E96, ASTM D1653, TAPPI T464.)

Items	Model	C360M	C360H	W3/03I
Testing Efficiency	0.01g/(m ² ·day)~0.5g/(m ² ·day)	>24 hours	>24 hours	Accuracy 0.01 g/m ² ·24h
	0.5g/(m ² ·day)~5g/(m ² ·day)	12~24 hours	12~24 hours	Resolution 0.0001 g
	>5g/(m ² ·day)	≤8 hours	≤12 hours	
Max. Test Range	Water Method	10000/n (1~6) g / (m ² ·day) 645/n (1~6) g / (100in ² ·day)	10000/n (1~12) g / (m ² ·day) 645/n (1~12) g / (100in ² ·day)	0.1 ~ 10,000 g/m ² ·24h (standard)
	Desiccant Method	1200g / (m ² ·day) per piece 77g / (100in ² ·day) per piece	1200g / (m ² ·day) per piece 77g / (100in ² ·day) per piece	/
Test Station		6	12	1~3 with independent test results
Test Temperature	℃	20~55±0.2	20~55±0.2	15 C ~ 55 C ±0.1 C (standard)
Test Humidity	RH	10%~90%±1%	10%~90%±1%	10%~98%±1%
Photos				

C Electrolytic Sensor (Complies with ISO 15106-3.)

Items	Model	C330H
Test Range	g/(m ² ·d) (Standard)	0.005 ~ 50
	g/(pkg·d) (Package)	0.000025 ~ 0.25
Resolution	g/(m ² ·d)	0.001
Repeatability	g/(m ² ·d)	0.005 or 2%, whichever is greater
Test Temperature	℃	10 ~ 55 ±0.2
Test Humidity	RH	5% ~ 90% ±1%, 100%



3 Tensile Strength

This series of instruments can be used for the determination of physical and mechanical properties of plastic films, composite materials, adhesives, adhesive tapes, release paper, protective films, flip off caps, foils, rubber, paper fiber, etc.
Complies with ISO 37, ASTM E4, ASTM D882, ASTM D1938, ASTM D3330, ASTM F88, ASTM F904, JIS P8113.

Model	i-Strentek 1510	C610M	C610H	XLW[PC]	XLW	MED-01
Items						
Load Cell Capacity	500N (Standard) 50N, 100N, 250N, 1000N, 2000N, 5000N, 10000N (Optional)	500 N (standard) 50 N, 100 N, 250 N, 1000 N (optional) 5N (Customization available)	500 N (standard) 50 N, 100 N, 250 N, 1000 N (optional)	500 N (standard) 50 N, 100 N, 250 N (optional)	500 N (standard) 30 N, 50 N, 100 N, 200 N (optional)	250 N (standard) 50 N, 100 N, 500 N (optional)
Accuracy	1% FS	±0.5% of indicated value (2%FS~100%FS) ±0.01%FS (0% ~ 2%FS)	±0.5% of indicated value (2%FS~100%FS) ±0.01%FS (0% ~ 2%FS)	0.5% FS	1% FS	Better than 0.5% FS
Number of Specimens	1	1	1	1	1	1
Test Speed	1~500 mm/min	0~500 mm/min	0.05~500 mm/min	50, 100, 150, 200, 250, 300, 500 mm/min		Forward:10/50/100/150/200/300 mm/min Backward:10/50/100/150/200/300 mm/min
Stroke	800 mm	950 mm (customization available for 1200mm)	1000 mm	1000 mm	600 mm	600 mm
Photos						

4 Coefficient of Friction Tester

Friction tester is a kind of testing equipment which is used to measure coefficient of friction (COF) for materials. Basically, there are two kinds of coefficients: static coefficient of friction and kinetic coefficient of friction. Conforms to the standards: ISO 8295, ISO 8510-2, ASTM D1894, ASTM D4917, ASTM D3330, TAPPI T816, TAPPI T549.

Items	Model	C620H	MXD-02	COF-P01
Test Range		0 ~ 5 N (standard); 0~10 N, 0~30 N, 0~50N, 0~100N (optional)	0 ~ 5 N	Angle Range 0° ~ 85°
Accuracy		Displayed Value $\pm 0.5\%$ (10%FS~100%FS) $\pm 0.05\%$ FS (0%~10% of the load cell range)	0.5%FS	Accuracy 0.01°
Stroke		10 ~ 300 mm	70 mm, 150 mm	Angular Velocity 0.1°/s ~ 10.0°/s
Sled		Weight: 200g; Size: 63.5mm x 63.5mm Customization is available	200 g (Standard) Sled of specific weight could be customized	1300g (standard); 235g (optional); 200g (optional) Customization is available for other masses
Test Speed		0 ~ 500 mm/min (Any integer within this range can be set)	100 mm/min, 150 mm/min	/
Test Temperature		Room Temperature ~ 100 °C	/	/
				

5 Heat Seal and Hot Tack

Heat Seal Testers can be used to determine the heat seal temperature, pressure, and dwell time for plastic films, plastic composite films, paper-plastic composite films, coextruded films, aluminized films, aluminum foils, and aluminum-foil composite films. Heat sealing surface can be customized as customer required. Complies with ASTM F2029.

Hot Tack Testers are professionally designed for Hot tack and heat seal performance tests for plastic films, laminated films and other packaging films. Meanwhile, it can be used to test the peeling and tensile properties of adhesives, adhesive tapes, laminated films, plastic films, paper and other flexible materials. Complies with ASTM F1921.

Items	Model	C630H	HST-H3	C632M
Sealing Temperature		Room temperature ~ 300°C	Room temperature ~ 250°C	Room temperature ~ 250°C
Temperature Fluctuation		± 0.2 °C	± 0.2 °C	± 0.2 °C
Temperature Gradient		≤ 20 °C	N/A	N/A
Dwell Time		0.1 ~ 999.99 s	0.5 ~ 999.9 s	0.1 ~ 999.9 s
Sealing Pressure		0.1Mpa ~ 0.7 Mpa (14psi ~ 101psi)	0.05Mpa ~ 0.7 Mpa	0.05Mpa ~ 0.7 Mpa
Sealing Area		40 mm x 10 mm	330 mm x 10 mm (customization available)	100 mm x 10 mm
Number of Sealing Jaws		5 sealing jaws with independent temperature control	Single heating surface or double heating surfaces	/
Load Cell Capacity		/	/	50 N
Force Accuracy		/	/	1500、2000~12000 mm/min
Delay time		/	/	0.01 ~ 999.99
Photos				

6 Leak and Seal Strength Detector

Leak and Seal Strength Tester is professionally designed for the leakage tests of packages for food, drugs, medical instruments, household chemical products, cars, electronic components, stationeries and other industrial products. The instrument also can be used to test seal performance of specimens after falling and compression tests. Complies with ASTM D3078, ISO 11607-1, ISO 11607-2, ASTM F1140, ASTM F2054.

Items	Model	C660B	MFY-01	C660M
Vacuum Degree		0 ~ - 90KPa / 0 ~ -13 psi	0 ~ - 90KPa	Test Range 0 ~ 600 KPa; 0 ~ 87.0 psi (standard) 0 ~ 1.6 MPa; 0 ~ 232.1 psi (optional)
Accuracy		$\pm 0.25\%$ FS	1% FS	Resolution 0.1 KPa / 0.01 psi
Vacuum Chamber Effective Sizes		Φ270 mm x 210 mm (H) (standard) Φ360 mm x 585 mm (H) (optional) Φ460 mm x 330 mm (H) (optional) Note: customization is available for other sizes	Φ270 mm x 210 mm (H) (standard) Φ360 mm x 585 mm (H) (optional) Φ460 mm x 330 mm (H) (optional) Note: customization is available for other sizes	Pressure Accuracy $\pm 0.25\%$ FS
Gas Supply Pressure		0.5 MPa ~ 0.7 Mpa (73psi ~ 101psi)	0.7 MPa (outside of supply scope)	Pressure Accuracy 0.1s ~ 999999.9 s
Photos				


7 Falling Dart Impact Tester

The instruments are designed for the determination of the impact mass and energy that cause 50% plastic films or sheet samples failure under certain impacting conditions. Complies with ISO 7765-1-1988, ASTM D1709, JIS K7124-1.

Items	Model	BMC-BI	C670M	
Test Method		Method A or Method B is optional		
Test Range		Method A:50~2000 g ; Method B:300~2000 g		
Weight Accuracy		+0,5 %		

8 Thickness Tester

Thickness Testers utilize contacting method to provide accurate and precise thickness measurements for plastic films, sheets, paper, foils, silicon wafers and other materials. Complies with ISO 4593, ISO 534, ASTM D6988, ASTM F2251, ISO 3034, ISO 12625-3, ISO 5084, ASTM D374.

Items	Model	C640M	C640H	CHY-C2A
Test Range (Standard)		0 ~ 2 mm (Standard); 0~6, 0~12 (Optional)	0 ~ 2 mm (Standard); 0~6, 0~12 (Optional)	0 ~ 2 mm (Standard); 0~6, 12 (Optional)
Resolution		0.1 μ m	0.1 μ m	0.1 μ m
Repeatability ^{Note3}		0.8 μ m	0.4 μ m	N/A
Test Pressure		Film: 17.5 $\pm$ 1 KPa, Paper: 100 $\pm$ 1 KPa (Standard)/50 $\pm$ 1kPa (Optional),	Film: 17.5 $\pm$ 1 KPa, Paper: 100 $\pm$ 1 KPa (Standard)/50 $\pm$ 1kPa (Optional),	Film: 17.5 $\pm$ 1 KPa, Paper: 50 $\pm$ 1kPa (Optional),
Contact Area		Film: 50 mm ² Paper: 200 mm ²	Film: 50 mm ² Paper: 200 mm ²	50 mm ² (Film);200 mm ² (Paper) Note: Select one pressure foot for film or paper; customization is available.
Feeding Speed		1.5 ~ 80 mm/s (Adjustable)	1.5 ~ 80 mm/s (Adjustable)	/
Photos				

9 Tearing Tester

C680M Tearing Tester is designed for the tearing test of films, sheets, flexible PVC, PVDC, waterproof films, woven materials, polypropylene, polyester, paper, cardboard, textiles and nonwovens. Complies with ISO 6383-1-1983, ISO 6383-2-1983, ISO 1974, ASTM D1922, ASTM D1424.

Items	Model	C680M	
Pendulum Capacity		200gf, 400gf, 800gf, 1600gf, 3200gf, 6400gf	
Air Source Pressure		0.6 MPa (supplied by user)	
Net Weight of Mainframe		40kg (200gf basic pendulum)	

10 Headspace Gas Analyzer

Headspace Gas Analyzer is equipped with professional structural and high precision sensors. It can provide accurate and fast evaluation of the volume of oxygen and carbon dioxide (with optional accessories) in sealed packages, bottles, cans, etc. Because of its portable design, the instrument can be used to measure the volume and proportion of oxygen and carbon dioxide on production lines, at warehouses or in laboratories, to serve as a guide for production.

Items	Model	C650H	C650B	C650M
Testable Gases		O ₂ (Standard) CO ₂ (optional)	O ₂ (Standard) Electrochemistry CO ₂ (optional) Infrared Absorption	O ₂ (Standard) Electrochemistry CO ₂ (optional) Infrared Absorption
Test Range		0.2% ~ 21% 2% ~ 100%	0 ~ 100% 0 ~ 100%	0 ~ 100% 0 ~ 100%
Test Accuracy		$\pm$ 0.2% $\pm$ 2%	$\pm$ 0.3% $\pm$ (0.03% + displayed value * 5%)	$\pm$ 0.2% $\pm$ (0.03% + displayed value * 5%)
Sampling Volume		$\geq$ 5 mL (Standard Atmospheric Pressure) $\geq$ 20 mL (Standard Atmospheric Pressure)	6 ~ 8 mL (Standard Mode) 15 mL (Standard Mode)	<2 mL (Standard Mode) 15 mL (Standard Mode)
Photos				

11 Heating Shrinkage Tester

C631H Thermal Shrinkage Tester is designed and developed in accordance with ISO 14616 and GB/T 34848, for determination of shrinking force, contracting force and shrinkage ratio of heatshrinkable films. Shrinking force greater than 0.01N can be detected.

RSY-R2 Film Free Shrink Tester is professionally applicable to the determination of heating shrinking performance and dimensional stability of various films, heatshrinkable tubes, hard PVC films for tablets. Complies with ASTM D2732.

Items	Model	C631H	RSY-R2	
Load Cell Capacity		5 N (Standard) ;10 N, 30 N (Optional)	/	
Displacement Range		0.1 ~ 95 mm	/	
Temperature Range		Room Temperature ~ 210 °C	Room temperature ~ 200°C	
Temperature Accuracy		$\pm$ 0.5 °C (Single Point Calibration)	$\pm$ 0.3°C	
Number of Stations		1 Group (2 pcs)	/	
Specimen Size		110 mm x15 mm (Standard)	$\leq$ 140 mm x 140 mm	

12 Lasting Adhesive Tester & Primary Adhesive Tester

Lasting Adhesive Tester can be used to test the holding power of pressure-sensitive tapes, pressure-sensitive labels and protective films, etc.

Primary Adhesive Tester is designed based on the balling method, and the primary adhesive property of adhesive tapes could be obtained by observing adhesive effect occurred immediately after rolling ball and adhesive specimen come into contact. Complies with ASTM D3654.

Items	Model	CZY-85A		Items	Model	CZY-G	
Standard Roller		2000 g $\pm$ 50 g		Angle Range		0 ~ 60°	
Weight		1000 g $\pm$ 5g (with hook)		Panel Width		120 mm	
Test Plate A		125 mm (L) x 50 mm (W) x 1.3 mm (D)		Testable Area Width		80 mm	
Timing Range		0 ~ 9999 hrs 59 min 59 sec		Standard Steel Ball		1/32 inch ~ 1 inch	
Number of Stations		8		Instrument Dimension		320 mm (L) x 140 mm (W) x 180 mm (H)	

13 Digital Torque Tester

It is designed to measure the open force and lock force of the caps of bottles, spout bags and flexible tube packages. Complies with ASTM D2063, ASTM D3198, ASTM D3474.

Items	Model	C612M	NJY-20
Load Cell Capacity		5 Nm (Standard); 20 Nm (Optional); 40 Nm (Optional)	20 Nm (Standard); 40 Nm (Optional); 50 Nm (Optional)
Accuracy		Indicated Value $\pm 0.5\%$ (10%~100% of Load cell capacity)	1% FS
Resolution		0.0001 Nm	0.001 Nm
Clamp Range		(Body) $\Phi 5$ mm ~ $\Phi 170$ mm; (Cap) $\Phi 10$ mm ~ $\Phi 80$ mm	$\Phi 5$ mm ~ $\Phi 170$ mm (Diameter)
Statistical Analysis Allowance		0 ~ 999	1 ~ 9



14 Abrasion Resistance

This series of instruments can be used to measure abrasion resistance of surface layers (ink layer or photosensitive (PS) coating) of printed materials. They can analyze the problems of poor abrasion resistance, ink layer falling off, lower printable force, and poor hardness of coating layers of printed materials. Complies with ASTM D5264, TAPPI T830.

Items	Model	RT-01
Rub Pressure		8.9 N (2lb); 17.8 N (4lb)
Rub Speed		21, 42, 85, 106 cpm
Rub Times		0~999999
Number of Specimens		1~2



15 Box Compression Tester

Box Compression Tester can be used to measure the compressive resistance, deformation and stacking capability of cartons, beehive crates, plastic tanks, paper tanks, paper cases, IBC tanks and other packages. Complies with ASTM D642, ASTM D4169, ISO 12048.

Items	Model	C611B	C611M
Load Cell Capacity		9 KN (3 pcs)	9 KN (3 pcs)
Accuracy		Indicated Value $\pm 1\%$ (10% ~ 100% of load cell capacity)	Indicated Value $\pm 1\%$ (10% ~ 100% of load cell capacity)
Force Resolution		1 N	1 N
Deformation Resolution		0.1 mm	0.1 mm
Test Speed		0 ~ 200mm/min (Any integer within the specified range)	0 ~ 200mm/min (Any integer within the specified range)
Test Space		0.6 m (L) $\times$ 0.6 m (W) $\times$ 0.61 m (H)	0.8 m (L) $\times$ 0.8 m (W) $\times$ 0.61 m (H)
Photos			

16 Flex Durability Tester

It is applicable to the determination of flex durability of flexible films, composite films and coating films. The instrument can simulate the kneading and creasing behaviors of films happened during production, processing and transportation. Complies with ASTM F392.

Items	Model	C681M
Flex Frequency		45 cpm
Flex Angle		440° / 400°
Horizontal Stroke		155 mm / 80 mm
Number of Stations		4



17 Fogging Tester

It designed for the fogging characteristics evaluation of volatile constituents of decorating materials used in cars and aircrafts, e.g. plastic articles, polyurethane, textiles, leather, adhesives, nonwovens and thermal forming elastomers at high temperature conditions. It could be used for the fogging phenomenon test of high intensity discharge (HID) headlamps of cars. Complies with ISO 6452, DIN 75201, SAE J1756, BS EN 14288, PV 3920, PV 3015, ES-X83231, NES M0161, D45 1727, GM 9305P, TSM 0503G.

Items	Model	FT-F1
Temperature Range of High-Temperature Bath		Room temperature~150°C; (room temperature~280°C is optional)
Accuracy		$\pm 0.1^\circ\text{C}$ (150°C)
Temperature Range of Low-Temperature Bath		0~100°C
Accuracy		$\pm 0.1^\circ\text{C}$



18 Air Permeability Tester

TQD-G1A is professionally designed for the determination of air permeability of decorating materials used in cars, e.g. polyurethane, expanded plastics, PVC, leather, textiles, nonwovens and other materials. Through the test, physical characteristics of materials could be controlled to meet practical application requirements. Complies with ISO 9237, ISO 4638, ISO 5636, ASTM D737, TAPPI T460, JIS P8117.

Items	Model	TQD-G1A
Test Range of Pressure Difference		0~1000 Pa
Test Range of Flux		0~30 L/min
Sample Size		2" x 2" (5cm $\times$ 5cm)
Inter Face Size		$\Phi 8$ mm Polyurethane Pipe



Labthink Instruments Co., Ltd. (Labthink) was founded in 1989. It is a leading supplier of packaging testing instruments and solutions globally and also the world's first corporate partner of the World Packaging Organization (WPO). The operational headquarters is located in Jinan, Shandong, China, with international headquarters in Boston, USA, European branch in Frankfurt, Germany, Asia-Pacific branch in Kuala Lumpur, Malaysia, and an office in Dubai, UAE. With a presence in more than 70 countries and regions worldwide, Labthink is a multinational high-tech company dedicated to helping customers succeed, employees develop, and brands gain respect.

For more than 30 years, Labthink has been focusing on the field of packaging testing. Through continuous technological innovation, Labthink has developed over 200 patented technologies, including a major breakthrough in "independent core sensor technology." Labthink's cutting-edge product group, centered on the C series, covers performance testing for packaging and related materials, such as oxygen permeability, air permeability, water vapor permeability, mechanics, heat seal, hot tack, thermal shrinkage, coefficient of friction, thickness, impact resistance, seal & leakage, headspace gas analysis, adhesion, rubbing and many others.

Labthink ilac-MRA CNAS certified laboratory - Labthink Packaging Safety Testing Center, is known for its comprehensive testing capabilities and extensive collection of instruments. The laboratory covers an area of 410 square meters and is equipped with more than 120 sets of professional packaging instruments. The center offers reliable and accurate data services to help customers respond to development challenges and achieve commercial success. The experienced technical team receives samples from customers around the world, offering in-depth data analysis, problem diagnosis and customized testing solutions that meet unique needs, such as special samples, difficult tests, and tests that may involve danger and risk.

Labthink is committed to collaborating with the industry to advance the development of testing methods, theories, standards, and specifications. It plays an active role in promoting the standardization of the industry's data system and has already hosted and participated in the drafting of national standards for packaging materials testing. Leveraging its extensive experience and expertise, Labthink continues to promote "Inter-laboratory Test Data Proficiency Services" in China and North America. These initiatives help laboratories standardize their testing methods and enhance their testing capabilities, while promoting progress and development in the industry as a whole.

Labthink adheres to innovation and precision in its development strategy, constantly exploring new frontiers in microscopic testing to create new enterprise value and help the industrial chain continue to progress.

Labthink International, Inc. (USA)

200 River's Edge Drive, Medford, MA 02155, USA
Tel: +1-617-830 2190
Fax: +1-781-219 3638
E-mail: info@labthinkinternational.com
Website: www.labthinkinternational.com

Labthink Instruments Co., Ltd. (CHINA)

144 Wuyingshan Road, Jinan 250031, China
Tel: +86-531-58702937
Fax: +86-531-85062108
E-mail: trade.en@labthink.com

Labthink Sdn Bhd (APAC Customer Center)

Unit 3-1 & 3-2, Level 3, Menara Mudajaya, No.12A, Jalan PJU 7/3,
Mutiara Damansara, 47810 Petaling Jaya, Selangor, Malaysia
Phone: +603-79321136
Email: info@labthinkasia.com

Labthink GmbH (Europe)

Hermannstrasse 34A 63263 Neu-Isenburg | Germany
Phone: +49 6102 7807 990
E-mail: info@labthinkeurope.com

Labthink Middle East FZE LLC (Middle East)

A-5801-89 - Flamingo Villas, Ajman Media City,
Dubai, UAE
E-mail: info@labthinkeurope.com

