Hanli 汉立®
www.hanlichiller.com

Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance



Scan to see more

Add: No. 1, Second Road, XinFuYuan, Hannan District, Wuhan, China
Post Code: 430090
Email: hanli-laserchiller@hanlizl.com, liliang@hanlizl.com,
Tel: +86-13682641130 , +86-13627291204
Website:www.hanlichiller.com

WATER CHILLER FOR FIBER LASER SOURCE

WUHAN HANLI REFRIGERATION TECHNOLOGY CO., LTD.



Add: No. 1, Second Road, XinFuYuan, Hannan District,
Wuhan, China
Post Code: 430090
Email: hanli-laserchiller@hanlizl.com, liliang@hanlizl.com,
Tel: +86-13682641130 , +86-13627291204
Websites:www.hanlichiller.com

Professional quality. Pursuit of excellence

Focus on laser refrigeration technology industry
hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

Hanli 汉立®
Professional quality. Pursuit of excellence

WUHAN HANLI REFRIGERATION TECHNOLOGY CO., LTD.

Company profile

Wuhan Hanli Refrigeration Technology Co., Ltd. is a high-tech enterprise with a number of national technology patents. Founded in 1998, with a registered capital of 12 million RMB, Hanli specializes in the research and development, production, sales and after-sales service of fiber laser chillers. After more than 20 years of operation, Hanli has become an expert in the laser chiller industry. It has an excellent brand image in the laser cutting and laser welding industries and has been recognized and well-known in the laser market.

Wuhan Hanli has extensive cooperation with major domestic and foreign laser manufacturers and laboratories (such as Raycus, Max, IPG, China Academy of Engineering Physics, National Optoelectronics Laboratory, etc.). Hanli HL series laser chillers are equipped with fiber lasers With power ranging from 1000W to 120,000W, SCH, SY, and SCL series laser chillers are suitable for the currently popular 1000W to 3000W handheld laser welding. Diversified product series, UV laser chiller and Co2 laser chiller have gained high reputation in the market, Hanli cooperates with hundreds of well-known domestic laser machine manufacturers and institutions such as Bodor Laser, Senfeng Laser, Gweike Laser, Qingyuan Laser, HSG Laser, etc., as well as the Chinese













Academy of Sciences, China Institute of Engineering Physics, etc., Hundreds of thousands of laser chillers are located around the world, providing the most economical and environmentally friendly cooling solutions for laser cutting and welding customers.

The main features of Hanli chiller products are: stable performance, energy saving and environmental protection, clean water quality, compatible with all mainstream lasers in the market, full model coverage, providing 50Hz/60Hz. We have standardized production and sufficient stocking, and we have an excellent laboratory The test system fully simulates the operating environment of the laser chiller, and several laboratories simulate high temperature tests, low temperature tests, fatigue tests, vibration tests, etc. to ensure that our machines can maintain reliable and stable working performance under different ambient temperatures around the world. We have powerful testing equipment. We strictly test each machine before delivery. At the same time, we have a complete after-sales service system to provide customers with worry-free after-sales. Hanli will continue to adhere to the craftsmanship spirit of pursuing excellence and excellence, and continue to maintain the leading



Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance

Hanli 汉立®

WUHAN HANLI REFRIGERATION TECHNOLOGY CO., LTD.

Qualifications

Wuhan Hanli Refrigeration Technology Co., Ltd. is a high-tech enterprise that focuses on research and development and has a number of national technology patents. It has a strong technical research and development team and quality management system.

Specializing in the research and development, production, sales and after-sales service of chillers for laser cutting machines. After more than 20 years of operation and precipitation, Hanli has become one of the leaders in the laser cutting industry, has an excellent brand image in the industry, and has been recognized and understood by the laser market.

























38,866.15㎡

Company area

300+

Employees

40models

Laser chillers

2years

Free maintenance and worry-free after-sales service

30copyrights

Stable and reliable performance

33patents

Technical patent recognition quality assurance

Focus on laser refrigeration technology industry
hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

Hanli 汉立®

WUHAN HANLI REFRIGERATION TECHNOLOGY CO., LTD.

Rigorous quality management system

Purchasing

Strictly control and manage supply chain

Ensure that each component is compliant with

Pre-production control

Full inspection on key components

Aging test on key components

Production assembly process

Standardized technique implementation
Assemble the chillers in strict accordance with specific regulated manufacturing procedures

QC before delivery

Overall performance testing
Aging test and complete performance test must be performed on each finished chiller

Delivery

Deliver on time

Shorten the overall response cycle of supply chain

Customer service

2 years warranty

Lifetime maintenance and repair, 24/7 hotline service with quick response

Systematic warehouse management





Strictly control and manage supply chain. Perform regular aging test on core components. Ensure that each component is compliant with quality standard







Strictly implement modular mass production with process standardization. Achieve high quality and high efficiency production



Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

Hanli 汉立®

Fiber laser chiller

The specialized quality pursue is remarkable


Model	HL-1500-QG2/2	HL-1500-EH-QG2/2	HL-2000-QG2/2	HL-3000-QG2/2	HL-3000-EH-QG2/2
Voltage & Frequency	220V/AC±10% 50Hz	220V/AC±10% 60Hz	220V/AC±10% 50Hz	220V/AC±10% 50Hz	220V/AC±10% 60Hz
Rated power	2.3 kW	2.3 kW	2.8 kW	3.5 kW	3.5 kW
maximum current	9.2 A	9.2 A	12.8 A	16.5 A	16.5 A
Refrigeration capacity	4.7 kW	4.8 kW	6.7 kW	8.7 kW	8.7 kW
Compressor power	0.895 kW	0.83 kW	1.32 kW	1.48 kW	1.40 kW
Electric heating power	0.9 kW	0.9 kW	0.9 kW	0.9 kW	0.9 kW
Pump power	0.36 kW	0.36 kW	0.36 kW	0.63 kW	0.63 kW
Fan power	0.1 kW	0.121 kW	0.1 kW	0.18 kW	0.21 kW
Maximum air volume of the fan	1920 m^3./h	2070 m^3./h	1920 m^3./h	4400 m^3./h	4400 m^3./h
Rated Flow of the low temperature end	16.5 ~ 18 L/min		22 ~ 24 L/min	33 ~ 36 L/min	
Rated pressure of the low temperature end	3.0 bar		3.0 bar	3.0 bar	
Maximum pressure of low temperature end	5.6 bar		5.6 bar	4.5 bar	
Dimensions of the low temperature end interface	G1/2-Φ12 mm quick connector		G1/2-Φ16 mm quick connector	G3/4-Φ20 mm pagoda joint G1-Φ20 mm pagoda joint	
Water temperature setting range of low temperature end	21 ~ 32 ℃		21 ~ 32 ℃	21 ~ 32 ℃	
Rated Flow of the high temperature end	1.2 ~ 1.5 L/min		1.2 ~ 1.5 L/min	1.2 ~ 1.5 L/min	
Rated pressure of the high temperature end	3.0 bar		3.0 bar	3.0 bar	
Dimensions of the high temperature end interface	G1/2-Φ10 mm quick connector		G1/2-Φ10 mm quick connector	G1/2-Φ10 mm quick connector	
Water temperature setting range of high temperature end	26 ~ 35 ℃		26 ~ 35 ℃	26 ~ 35 ℃	
Water temperature control accuracy	22 ~ 29.5 ℃		22 ~ 29.5 ℃	22 ~ 29.5 ℃	
Water Tank	15 L		15 L	28 L	
Application environment	-20 ~ 40 ℃		-20 ~ 40 ℃	-20 ~ 40 ℃	
Coolant	R32		R32	R32	
Electric heating power	Orange pattern white		Orange pattern white	Orange pattern white	
Noise Level	≈64 dB(A)		≈75 dB(A)	≈72 dB(A)	
Machine dimension & Net weight	515×430×725 mm(L*W*H) 37 kg		515×430×725 mm(L*W*H) 41 kg	565×500×815 mm(L*W*H) 55 kg	
Packaging size & Gross weight	555×490×870 mm(L*W*H) 43 kg		555×490×870 mm(L*W*H) 47 kg	640×560×970 mm(L*W*H) 63 kg	
Suitable cooling medium	Pure water, glycol solution(concentration ≤ 30%)		Pure water, glycol solution(concentration ≤ 30%)	Pure water, glycol solution(concentration ≤ 30%)	

Note:The working current can be different under different working conditions.The above information is for reference only.Please subject to the actual delivered product.













Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

Hanli 汉立®

Fiber laser chiller


The specialized quality pursue is remarkable

Model	HL-4000-QG2/2	HL-6000-QG2/2	HL-6000-EH-QG2/2	HL-8000-QG2/2
Voltage & Frequency	220V/AC±10% 50Hz	220V/AC±10% 50Hz	220V/AC±10% 60Hz	380V/AC±10% 50Hz
Rated power	4.5 kW	7.6 kW	7.6 kW	9.7 kW
maximum current	20.5 A	28 A	28 A	18.5 A
Refrigeration capacity	11.3 kW	19.1 kW	19.1 kW	15.2 kW
Compressor power	1.94 kW	1.48×2 kW	1.4×2 kW	4.15 kW
Electric heating power	1.25/0.8 kW	1.25/1.4 kW	1.25/1.4 kW	1.6/1.4 kW
Pump power	0.88 kW	0.88 kW	0.88 kW	1.85 kW
Fan power	0.18 kW	0.208×2 kW	0.208×2 kW	0.75 kW
Maximum air volume of the fan	4500 m³./h	3955×2 m³./h	3955×2 m³./h	8400 m³./h
Rated Flow of the low temperature end	40 ~ 44 L/min	60 ~ 66 L/min		80 ~ 88 L/min
Rated pressure of the low temperature end	3.0 ~ 4.0 bar	4.0 bar		4.0 bar
Maximum pressure of low temperature end	4.1 bar	6.0 bar		5.2 bar
Dimensions of the low temperature end interface	G1-Φ25 mm pagoda joint G3/4-Φ25 mm pagoda joint	G1-Φ25 mm pagoda joint G3/4-Φ25 mm pagoda joint		G1-Φ25 mm pagoda joint
Water temperature setting range of low temperature end	21 ~ 32 ℃	21 ~ 32 ℃		21-32 ℃
Rated Flow of the high temperature end	1.5 ~ 2.0 L/min	2.0 L/min		2.3 L/min
Rated pressure of the high temperature end	3.0 ~ 4.0 bar	3.5 bar		4.0 bar
Dimensions of the high temperature end interface	G1/2-Φ12mm quick connector	G1/2-Φ12 mm quick connector		G1/2-Φ12 mm quick connector
Water temperature setting range of high temperature end	26 ~ 35 ℃	26-35 ℃		26-35 ℃
Water temperature control accuracy	22 ~ 29.5 ℃	22 ~ 29.5 ℃		22 ~ 29.5 ℃
Water Tank	55 L	55 L		77 L
Application environment	-20 ~ 40 ℃	-20 ~ 40 ℃		-20 ~ 40 ℃
Coolant	R32	R32		R32
Electric heating power	Orange pattern white	Orange pattern white		Orange pattern white
Noise Level	≈75 dB(A)	≈75 dB(A)		≈74 dB(A)
Machine dimension & Net weight	610×665×1000 mm(L*W*H) 70 kg	1040×510×890 mm(L*W*H) 104 kg		815×710×1065 mm(L*W*H) 117 kg
Packaging size & Gross weight	725×670×1035 mm(L*W*H) 76 kg	1100×570×960 mm(L*W*H) 111 kg		875×760×1140 mm(L*W*H) 122 kg
Suitable cooling medium	Pure water, glycol solution(concentration ≤ 30%)	Pure water, glycol solution(concentration ≤ 30%)		Pure water, glycol solution(concentration ≤ 30%)
Note:The working current can be different under different working conditions.The above information is for reference only.Please subject to the actual delivered product.				













Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

Fiber laser chiller

The specialized quality pursue is remarkable


Model	HL-12000-QG2/2	HL-12000-EH-QG2/2	HL-20000-QG2/2	HL-20000-EH-QG2/2	HL-30000-QG2/2	HL-30000-EH-QG2/2
Voltage & Frequency	380V/AC±10% 50Hz	380V/AC±10% 60Hz	380V/AC±10% 50Hz	380V/AC±10% 60Hz	380V/AC±10% 50Hz	380V/AC±10% 60Hz
Rated power	15.2 kW	15.2 kW	20.0 kW	20.0 kW	30.0 kW	30.0 kW
maximum current	26.5 A	26.5 A	40.0 A	40.0 A	55.0 A	55.0 A
Refrigeration capacity	35 kW	35 kW	50.0 kW	50.0 kW	73.0 kW	73.0 kW
Compressor power	5.99 kW	5.35 kW	9.820 kW	9.303 kW	13.2 kW	15.1 kW
Electric heating power	1.6/2.4 kW	1.6/2.4 kW	3.0/5.0 kW	3.0/5.0 kW	0.8/10.0 kW	0.8/10.0 kW
Pump power	2.2 kW	2.2 kW	3.0 kW	3.0 kW	0.36/4.0 kW	0.36/5.0 kW
Fan power	0.55 kW	0.75 kW	0.55×2 kW	0.75×2 kW	0.95×2 kW	0.95×2 kW
Maximum air volume of the fan	8400 m^3./h	8450 m^3./h	8400×2 m^3./h	8450×2 m^3./h	11000×2 m^3./h	11000×2 m^3./h
Rated Flow of the low temperature end	120 ~ 132 L/min	120 ~ 132 L/min	≥200 L/min	≥200 L/min	≥280 L/min	≥280 L/min
Rated pressure of the low temperature end	4.0 bar		5.0 bar		5.5 bar	
Maximum pressure of low temperature end	7.0 bar		6.6 bar		6.5 bar	
Dimensions of the low temperature end interface	G1-Φ25 mm pagoda joint		G1/2-Φ32 mm pagoda joint x2		G2-ϕ38 mm pagoda joint x2	
Water temperature setting range of low temperature end	21 ~ 32 ℃		21 ~ 32 ℃		21-26 ℃	
Rated Flow of the high temperature end	3 L/min		4.5 L/min		5.5 L/min	
Rated pressure of the high temperature end	4.0 bar		5.0 bar		5.5 bar	
Dimensions of the high temperature end interface	G1/2-Φ12 mm quick connector		G2-Φ13 mm pagoda joint x2		G1/2-Φ20 mm pagoda joint x2	
Water temperature setting range of high temperature end	26 ~ 35 ℃		26 ~ 35 ℃		26 ~ 35 ℃	
Water temperature control accuracy	22 ~ 29.5 ℃		±1 ℃		±1 ℃	
Water Tank	95 L		160 L		240 L	
Application environment	-20 ~ 40 ℃		-20 ~ 40 ℃		-20 ~ 40 ℃	
Coolant	R32		R32		R32	
Electric heating power	Orange pattern white		Orange pattern white		Orange pattern white	
Noise Level	≈64 dB(A)		≈75 dB(A)		≈75 dB(A)	
Machine dimension & Net weight	740×810×1030 mm(L*W*H) 145 kg		1590×750×1010 mm(L*W*H) 247 kg		1835×840×1130 mm(L*W*H) 318 kg	
Packaging size & Gross weight	795×860×1110 mm(L*W*H) 155 kg		1670×815×1060 mm(L*W*H) 256 kg		2045×900×1135 mm(L*W*H) 388 kg	
Suitable cooling medium	Pure water, glycol solution(concentration ≤ 30%)		Pure water, glycol solution(concentration ≤ 30%)		Pure water, glycol solution(concentration ≤ 30%)	

Note:The working current can be different under different working conditions.The above information is for reference only.Please subject to the actual delivered product.













Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

Fiber laser chiller

The specialized quality pursue is remarkable

Model	HL-40000-QG2/2	HL-40000-EH-QG2/2	HL-60000-QG2/2
Voltage & Frequency	380V/AC±10% 50Hz	380V/AC±10% 60Hz	380V/AC±10% 50Hz
Rated power	40 kW	42 kW	55.5 kW
maximum current	75 A	78 A	105 A
Refrigeration capacity	97 kW	97 kW	142 kW
Compressor power	9.820×2 kW	9.303×2 kW	13.24×2 kW
Electric heating power	0.8/15.0 kW	0.8/15.0 kW	0.8/19.35 kW
Pump power	0.36/3.5×2 kW	0.36/3×2 kW	0.36/3.5×3 kW
Fan power	0.65×4 kW	0.75×4 kW	0.95×4 kW
Maximum air volume of the fan	8400×4 m^3./h	8450×4 m^3./h	11400×4 m^3./h
Rated Flow of the low temperature end	≥400 L/min	≥400 L/min	≥600 L/min
Rated pressure of the low temperature end	5.0 bar		5.5 bar
Maximum pressure of low temperature end	6.5 bar		6.5 bar
Dimensions of the low temperature end interface	G2-Φ38 mm pagoda joint x4		G1 1/2-ϕ45 mm pagoda joint x4
Water temperature setting range of low temperature end	21 ~ 26 ℃		21 ~ 26 ℃
Rated Flow of the high temperature end	5 L/min		5.5 L/min
Rated pressure of the high temperature end	5.0 bar		5.5 bar
Dimensions of the high temperature end interface	G1/2-Φ20 mm pagoda joint x2		G1/2-Φ20 mm pagoda joint x2
Water temperature setting range of high temperature end	26 ~ 35 ℃		26 ~ 35 ℃
Water temperature control accuracy	±1 ℃		±1 ℃
Water Tank	360 L		470 L
Application environment	-20 ~ 40 ℃		-20 ~ 40 ℃
Coolant	R32		R32
Electric heating power	Orange pattern white		Orange pattern white
Noise Level	≈76 dB(A)		≈75 dB(A)
Machine dimension & Net weight	1670×1515×1295 mm(L*W*H) 624 kg		1980×1680×1320 mm(L*W*H) 764 kg
Packaging size & Gross weight	1770×1560×1335 mm(L*W*H) 645 kg		2015×1730×1350 mm(L*W*H) 806 kg
Suitable cooling medium	Pure water, glycol solution(concentration ≤ 30%)		Pure water, glycol solution(concentration ≤ 30%)


Note:The working current can be different under different working conditions.The above information is for reference only.Please subject to the actual delivered product.















Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

HanLi 汉立®

Handheld laser welding chiller

The specialized quality pursue is remarkable

Model	SCH-1500		SCH-2000		SCH-3000	
Voltage & Frequency	AC 1p 220V 50Hz	AC 1p 220V 60Hz	AC 1P 220 V 50Hz	AC 1p 220V 60Hz	1P 220V 50Hz	1P 220V 60Hz
Woking current of the whole machine	9.5 A	10.9 A	10.5 A	10.9 A	14 A	14 A
Mechanical and electrical power	2.1 kW	2.4 kW	2.3 kW	2.4 kW	3.1 kW	3.1 kW
Appkucatuib environment	-20℃<Environment temperature<40℃, Rrlative humidity<95%		-20℃<Environment temperature<40℃, Rrlative humidity<95%		-20℃<Environment temperature<40℃ Rrlative humidity<95%	
Tempe.control accuracy	22 ~ 29.5 ℃		22 ~ 29.5 ℃		±1℃	
Cooling capacity	4.5 kW		5.6kW		7.3kW	
Auxiliary heating power	800W (normal temperature)		800W (normal temperature)		800W (normal temperature)	
Refrigerant	R32		R32		R32	
Rated flow of water pump	1.2 m^3 / h		1.6 m^3 / h		1.6 m^3 / h	
Max.pump lift	40 m	68 m	68 m		68 m	
Pump power	0.26 kW	0.32 kW	0.32 kW		0.36 kW	
Tank volume	15 L		15 L		24 L	
Lasre nozzle interface	Φ12 mm Pneumatic PU tube		Φ12 mm Pneumatic PU tube		G1/2*Φ20 mm Pagoda hose connector	
Cugtting head nozzle interface	Φ6 mm Pneumatic quick plug connector		Φ6 mm Pneumatic quick plug connector		Φ6 mm Quick connector	
Size and weight of the machine	745×485×430 mm(L*W*H) 27 kg		745×485×430 mm(L*W*H) 29 /27 kg		860×485×430 mm(L*W*H) 48 kg	
Packing size and weight	800×515×58 mm(L*W*H) 35 kg		800×515×580 mm(L*W*H) 37/35 kg		920×510×560 mm(L*W*H) 57kg	
Functional characteristics	High efficiency and environmental protection, dual temperature and dual control, flow and over-temperature alarm, compressor thermal protection, air circuit breaker					
Recommended matching	1500w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)		2000w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)		3000w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)	
Note:The working current can be different under different working conditions.The above information is for reference only.Please subject to the actual delivered product.						




















Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

Hanli 汉立®

Handheld laser welding cabinet with built-in chiller

The specialized quality pursue is remarkable

Model	SCHYTJ-1500	SCHYTJ-2000		SCHYTJ-3000	
Voltage & Frequency	AC 1p 220V 50Hz	AC 1p 220V 50Hz	AC 1p 220V 60Hz	AC 1P 220V 50Hz	AC 1p 220V 60Hz
Woking current of the whole machine	8.6 A	12.7 A	11.8 A	15 A	12.9 A
Mechanical and electrical power	1.9 kW	2.8 kW	2.6 kW	3.9 KW	3.9 kW
Appkucatuib environment	-20℃<Environment temperature<40℃, Rrlative humidity<95%	-20℃<Environment temperature<40℃, Rrlative humidity<95%		-20℃<Environment temperature<40℃, Rrlative humidity<95%	
Tempe.control accuracy	22 ~ 29.5 ℃	22 ~ 29.5 ℃		22 ~ 29.5 ℃	
Cooling capacity	4.5 kW	5.6kW		6.75 kW	
Auxiliary heating power	600W (normal temperature)	600W (normal temperature)		900W (normal temperature) 650W (low temperature)	
Refrigerant	R32	R32		R32	
Rated flow of water pump	1.0 m^3/h	1.6 m^3/h		1.6 m^3/h	
Max.pump lift	20 m	33 m		33 m	
Pump power	0.18 kW	0.36 kW		0.36 kW	
Tank volume	20 L	20 L		28 L	
Lasre nozzle interface	Φ12 Pneumatic PU tube	Φ12 Pneumatic PU tube		G1/2*ϕ20mm Pagoda hose connector	
Cugtting head nozzle interface	Φ6mm Pneumatic quick insert connector	Φ6mm Pneumatic quick insert connector		Φ6mm Pneumatic quick insert connector	
Size and weight of the machine	985×420×705 mm(L*W*H) 49 kg	985×420×705 mm(L*W*H) 49 kg		1115×525×1040 mm(L*W*H) 79 kg	
Packing size and weight	1045×486×860 mm(L*W*H) 58 kg	1045×486×860 mm(L*W*H) 58 kg		1190×585×1200 mm(L*W*H) 95 kg	
Functional characteristics	High efficiency and environmental protection, dual temperature and dual control, flow and over-temperature alarm, compressor thermal protection, air circuit breaker				
Recommended matching	1500w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)	2000w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)		3000w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)	
Note:The working current can be different under different working conditions.The above information is for reference only.Please subject to the actual delivered product.					




















Focus on laser refrigeration technology industry

hole the core needs of customers with high stability and high cost performance

Service hotline: 400-8556-775

Handheld laser welding chiller without chassis

The specialized quality pursue is remarkable

Model	SCL-1500		SCL-2000		SCL-3000
Voltage & Frequency	AC 1p 220V 50Hz	AC 1p 220V 60Hz	AC 1p 220V 50Hz	AC 1p 220V 60Hz	AC 1P 220V 50Hz
Woking current of the whole machine	9.5 A	11.0 A	11.4 A	11.0 A	11.5 A
Mechanical and electrical power	2.1 kW	2.3 kW	2.3 kW	2.3 kW	3.0 kW
Appkucatuib environment	-20℃<Environment temperature<40℃ Rrlative humidity<95%		-20℃<Environment temperature<40℃ Rrlative humidity<95%		-20℃<Environment temperature<40℃ Rrlative humidity<95%
Tempe.control accuracy	22 ~ 29.5 ℃		22 ~ 29.5 ℃		22 ~ 29.5 ℃
Cooling capacity	4.5 kW	5.6 kW	5.6 kW		7.1 kW
Auxiliary heating power	800W (normal temperature)		800W (normal temperature)		800W (normal temperature)
Refrigerant	R32		R32		R32
Rated flow of water pump	1.0 m^3 / h	1.6 m^3 / h	1.6m^3/h		1.6 m^3/h
Max.pump lift	20 m	33 m	33 m		68 m
Pump power	0.18 kW	0.36 kW	0.36 kW		0.36 kW
Tank volume	15 L		15 L		24 L
Lasre nozzle interface	G1/2*Φ12mm Quick connector		G1/2*Φ12mm Quick connector		G1/2*ϕ20mm Pagoda hose connector
Cugtting head nozzle interface	G1/2*Φ6mm Quick connector		G1/2*Φ6mm Quick connector		G1/2*Φ6mm Quick connector
Size and weight of the machine	970×422×435 mm(L*W*H) 29 kg		970×422×435 mm(L*W*H) 29 kg		1060×522×525 mm(L*W*H) 45 kg
Packing size and weight	1020×452×580 mm(L*W*H) 40 kg		1020×452×580 mm(L*W*H) 40 kg		1110×700×500 mm(L*W*H) 53 kg
Functional characteristics	High efficiency and environmental protection, dual temperature and dual control, flow and over-temperature alarm, compressor thermal protection, air circuit breaker				
Recommended matching	1500w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)		2000w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)		3000w Continuous fiber laser (match with BWT,Max,Raycus,Reci source brands and so on)
Note:The working current can be different under different working conditions.The above information is for reference only.Please subject to the actual delivered product.					















